

SEP 07 2006

Tyco Docket No. 18060 (20958-2113)

Via Facsimile Transmission 571.273.8300

IN THE CLAIMS

1. (Previously Presented) A connector insertion and removal tool for inserting and removing an electrical connector onto and from a circuit board having opposite first and second surfaces, said tool comprising:

an installation mechanism configured to be positioned proximate the first surface of the circuit board; and

an extraction mechanism configured to be positioned proximate the second surface of the circuit board, said installation and extractor mechanisms being coupled to one another;

wherein at least one of said installation and extraction mechanisms comprises an actuator adapted for movement toward and away from the circuit board insert and remove the connector onto and from the circuit board.

2. (Previously Presented) A tool in accordance with Claim 1 wherein said installation mechanism and said actuator include a groove and rib combination extending toward the first surface to guide said actuator toward and away from said the circuit board during insertion of the connector.

3. (Previously Presented) A tool in accordance with Claim 1 wherein the includes a pin aperture field, said actuator comprising a plurality of extraction pins aligning with and extending into the pin aperture field on the second surface of the circuit board to remove the connector from the first surface of the circuit board.

4. (Previously Presented) A tool in accordance with Claim 1 further comprising at least one guide pin, said guide pin engaged to installation mechanisms on the first surface of the circuit board and engaged to said extraction mechanism on the second side of the circuit board.

5. (Previously Presented) A tool in accordance with Claim 4 wherein said extraction mechanism includes support plates holding said actuator therebetween, said support plates being

Tyco Docket No. 18060 (20958-2113)

Via Facsimile Transmission 571.273.8300

held stationary against the second surface of the circuit board while the actuator moves toward and away from the circuit board.

6. (original) A tool in accordance with Claim 1 further comprising nonconductive sections situated adjacent said actuator, thereby avoiding a conductive path through said tool.

7. (Previously Presented) A tool in accordance with Claim 1 wherein said at least one of said installation mechanism and said extraction mechanism comprises an alignment member configured to position the electrical connector with respect to a pin aperture field in the circuit board.

8. (Previously Presented) A tool in accordance with Claim 1 wherein each of said installation mechanism and said extraction mechanism comprises a plurality of modular blocks mounted on and held stationary with respect to the circuit board, and at least one movable block configured to move toward and away from the circuit board.

9. (Previously Presented) A tool in accordance with Claim 1 wherein said at least one said installation mechanism and said extraction mechanism comprises a positioning plate configured for sliding engagement with a guide track.

10. (Withdrawn) A connector insertion and removal tool for inserting and removing an electrical connector onto and from circuit board having opposed first and second surfaces, said tool comprising:

a first portion configured for coupling to the first surface of the circuit board and comprising a first actuator, said first actuator movable toward the first surface of the circuit board to disengage a first connector from the second surface of the circuit board, said first actuator movable away from the circuit board to permit engagement of a second connector to the second surface of the circuit board; and

a second portion coupled to said first portion, said second portion configured to be located proximate the second surface of the circuit board, said second portion comprising a

Tyco Docket No. 18060 (20958-2113)

Via Facsimile Transmission 571.273.8300

second actuator, said second actuator movable toward the second surface of the circuit board to engage the second connector to the circuit board, and said second actuator movable away from the circuit board to permit disengagement of the first connector from the circuit board.

11. (Withdrawn) A tool in accordance with Claim 10 further comprising a guide pin insertable through the circuit board, said first portion and said second portion engaged to said guide pin on opposite sides of the circuit board.

12. (Withdrawn) A tool in accordance with Claim 11 wherein said first portion comprises a first alignment member for engaging a first portion of said guide pin, and said second portion comprising a second alignment member for engaging a second portion of said guide pin.

13. (Withdrawn) A tool in accordance with Claim 10 wherein each of said first and second portions comprises modular blocks, at least some of said modular blocks being nonconductive.

14. (Withdrawn) A tool in accordance with Claim 10, at least one of said first portion and said second portion comprising a positioning plate, said positioning plate slidably engaged to a guide track to align the connector and the circuit board.

15. (Withdrawn) A tool in accordance with Claim 10 wherein said first actuator comprises an actuator block comprising a plurality of extraction pins.

16. (Withdrawn) A connector insertion and removal tool for inserting and removing an electrical connector onto and from a circuit board having opposed first and second surfaces, said tool comprising:

a first portion comprising a first plurality of modular blocks, said first plurality of modular blocks comprising a first pair of stationary alignment blocks configured to be held stationary against the a first surface of the circuit board, a first movable actuator block movable toward the first surface of the circuit board to disengage a first connector from the surface of the

Tyco Docket No. 18060 (20958-2113)

Via Facsimile Transmission 571.273.8300

circuit board and movable away from the circuit board to permit engagement of a second connector to the circuit board; and

a second portion comprising a second plurality of modular blocks, said second plurality of modular blocks comprising at least a second pair of stationary alignment blocks configured to be held stationary against the second surface of the circuit board, a second movable actuator block movable toward the second surface of the circuit board to engage the second connector to the circuit board and movable away from the circuit board to permit disengagement of the first connector from the circuit board.

17. (Withdrawn) A tool in accordance with Claim 16 further comprising a pair of guide pins, each of said first pair of alignment blocks and said second pair of alignment blocks configured to engage one end of said guide pins.

18. (Withdrawn) A tool in accordance with Claim 16 further comprising a pair of guide pins, each of said first pair of alignment blocks and said second pair of alignment blocks comprising a pair of alignment members extending therethrough and configured to engage a portion of said guide pins.

19. (Withdrawn) A tool in accordance with Claim 16 wherein said first movable actuator comprises a plurality of extraction pins that extend into a pin aperture field on the first surface to force the first connector from the second surface.

20. (Withdrawn) A tool in accordance with Claim 16 further comprising a pair of guide pins connecting said first portion and said second portion, each of said guide pins having a first ends having a first threaded portion and a second end having a second threaded portion, said first threaded portion being different from said second threaded portion.

21. (Withdrawn) A tool in accordance with claim 20 wherein a portions of said first threaded portion is removed, thereby preventing threads of said first threaded portion from engaging a complementary threaded alignment member.